

Grille Installation Instruction

Rev. 130701

Part#	GF	GR14FED09A		Application 04		~06 Nissan Maxima – Low Bumper Billet Grille					
	Iten	Part Name	QTY	QTY Description		Item	Part Name		QTY	Description	
Parts List	1	Billet Grille	1	Aluminum		3	U-Clip Nut		4	8#	
	2	'J' Hooks	4			4	Truss Socket	Tapping Screws	4	8×1″	
Install Notes: Overlay Replacement					×	Drill × Cut ×					
Step	Description					illustration					
1	Identify the grille & hardware with parts list.					#	*				
2	Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell.										
3	Center the billet grille into the opening of the factory grille shell. Secure the screw to the threaded holes on the front of the grille.Be sure the screws are through the OEM grille shell.										
4	Secure billet grille using the u-clip nuts and J hooks from the back side of the OEM grille shell.										
5	Make sure the billet grille is centered and tighten the fasteners.					N/A					
6	Reinstall the black plastic cover which was removed in step 2.						N/A				
7	Installation completed!!!										

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.

Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.

We are not responsible for any damage caused by the installation. Thank you for choosing our product!