

Grille Installation Instruction

Rev. 130701

Part#		GR14FED09C		Application F		For 200	2004-2006 Nissan Maxima					
Danta		ltem	Part Nan	ne QTY	Description		Item	Part	Name	QTY	Description	
Parts List		1	Billet Grille	e 1	Stainless steel		3	U-Clip Nut		4	8#	
		2	'J' Hooks	4	4		4	Truss Socket	Tapping Screws	4	8×1″	
Install	Note	es: O	verlay	√ Rep	Replacement ×							
Step	Description						illustration					
1	Identify the grille & hardware with parts list.											
2	Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell.											
3	Center the billet grille into the opening of the factory grille shell. Secure the screw to the threaded holes on the front of the grille.Be sure the screws are through the OEM grille shell.											
4	Sec	ure bill	et grille usin ack side of t	ng the u-clip n he OEM grille	outs and e shell.	J hooks		(gancus»			")	
5		ce sure fastenc		ille is centere	d and ti	ghten	N/A					
6	Reinstall the black plastic cover which was removed in step 2.							N/A				
7	Installation completed!!!											

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.

Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.

We are not responsible for any damage caused by the installation. Thank you for choosing our product!