

## Grille Installation Instruction

Part#		GR14FED09J		Applicatior		on	For 2004-2006 Nissan Maxima						
		ltem	Part Na	me	QTY	Des	cription	ltem	Part	t Name	QTY	Description	
Parts List	•	1	Billet Grille		1 Stain		ess steel	3	U-Clip Nut		4	8#	
		2	'J' Hooks		4			4	Truss Socket	Tapping Screws	4	8×1″	
Install	Note	lotes: Overlay 🗸 Replacement 🔀						Drill × Cut ×					
Step	Description							illustration					
1	Identify the grille & hardware with parts list.												
2	Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell.												
3	Center the billet grille into the opening of the factory grille shell. Secure the screw to the threaded holes on the front of the grille.Be sure the screws are through the OEM grille shell.												
4	Secure billet grille using the u-clip nuts and J hooks from the back side of the OEM grille shell.								همینیسی)			)	
5	Make sure the billet grille is centered and tighten the fasteners.							N/A					
6	Reinstall the black plastic cover which was removed n in step 2.								N/A				
7	Installation completed!!!												

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!