




Grille Installation Instruction

Rev. 180501

Part#	GR14FED29A&H	Application	For 2002-2003 Nissan Maxima GXE / SE Not For GLE/20th Anniversary of SE
-------	--------------	-------------	--

Parts List	Item	Part Name	QTY	Description	Item	Part Name	QTY	Description
	1	Billet Grille	2	Aluminum	3	Kep Nuts	8	10#-24
2	2- Hole Tabs	4		4	Slotted Studs	8	10#-24 × 3"	

Install Notes: Overlay Replacement Drill Cut

Step	Description	illustration
1	Identify the grille & hardware with parts list.	
2	Optional (for vehicles with black plastic cover under hood), pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. If you are still unable to access the rear, remove the grille shell and reattach after installation.	
3	Center the inserts into the opening and thread the slotted studs into the tabs welded the back of the grille using a slotted screwdriver. Then, secure it using 2-hole tabs and kep nuts provided, and tighten it from the rear.	
4	Reinstall the black plastic cover which was removed in step 2.	
5	Installation completed.	

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!