

Grille Installation Instruction

Rev. 150116

Part#	GR14FFD64H	Application	07~08 Nissan Maxima – Low Bumper Billet Grille
-------	------------	-------------	--

	Item	Part Name	QTY	Description	Item	Part Name	QTY	Description	
Parts Lis	st 1	Billet Grille	1	Aluminum	3	Screws	2	#8×1.25"	
	2	U-Nuts	2	8#	4	J Hooks	2	1.5"	
Install N	otes: Ov	verlay	eplacen	nent ×	Drill × Cut ×				
Step	Description				illustration				
1	Identify the grille & hardware with parts list.								
		e grille in place. Ce factory plastic radio							

N/A

N/A

Start to thread the J hooks onto the screws. Center N/A the grille in place. Wrap the hooks around plastic 4 bars in the openings. Use a Phillips screwdriver to

assembly. Now remove the factory grille shell; use

a small screwdriver to pull the center from each fastener. Release the four molded clips along the

Slide the u-nuts onto J hooks. Insert the screws into

5 Re-install the grille onto the vehicle.

N/A

6 Installation completed!!!

bottom of the grille.

the tabs on the billet. .

tighten the hardware.

2

3

N/A

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.

Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.

We are not responsible for any damage caused by the installation. Thank you for choosing our product!