

Grille Installation Instruction

Rev. 150116

Part# | GR14FFD64S | Application | 07~08 Nissan Maxima – Low Bumper Billet Grille

	Item	Part Name	QTY	Description	Item	Part Name	QTY	Description
Parts List	1	Billet Grille	1	Stainless steel	3	Screws	2	#8×1.25″
	2	U-Nuts	2	8#	4	J Hooks	2	1.5"

Install Notes: Overlay $\sqrt{}$ Replacement \times Drill \times Cut \times

Step	Description	illustration
1	Identify the grille & hardware with parts list.	
2	Test fit the grille in place. Open the hood and remove the factory plastic radiator cover and grille assembly. Now remove the factory grille shell; use a small screwdriver to pull the center from each fastener. Release the four molded clips along the bottom of the grille.	
3	Slide the u-nuts onto J hooks. Insert the screws into the tabs on the billet	N/A
4	Start to thread the J hooks onto the screws. Center the grille in place. Wrap the hooks around plastic bars in the openings. Use a Phillips screwdriver to tighten the hardware.	N/A
5	Re-install the grille onto the vehicle.	N/A
6	Installation completed!!!	N/A

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.

Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.

We are not responsible for any damage caused by the installation. Thank you for choosing our product!