

Grille Installation Instruction

Part#	# GR14FFE12V/E Application For 2007-2009 Nissan Altima Coupe												
		ltem	Part Na	me	QTY	Description		Item	Part Name		QTY	Description	
Parts L	ist	st 1 Billet Grille			1 Alum		num	3	Truss Head	Screws	8	6-32×1.5″	
		2 K-Lock Nuts		s	8 6-32			4	Metal Brack	ets	8		
Install N	Note	s: Ov	rerlay 🗸	Re	eplacen	nent	× C	orill 🖂	Cu	t ×			
Step	Description						illustration						
1	Identify the grille & hardware with parts list.												
2	Pop hood, remove plastic shroud at the top and set fasteners aside.												
3	Optional: Using factory instruction, remove the entire front grille shell.												
4	Position the grille onto grille shell cavity.												
5	Loosely attach the grille by holding the Metal Brackets behind factory grille shell and inserting the screws(from the front) through the billet grille holes and metal brackets, secure them with flange nuts provided.												
6	Once the billet grille are loosely attached, center them and tighten all screws at the same rate.												
7	Reinstall the plastic shroud with the fasteners removed in step 2.												
8	Installation completed!!!												

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.

We are not responsible for any damage caused by the installation. Thank you for choosing our product!