

Part#	GR14GEB19T	Application	08~10 Infiniti G37 Coupe
--------------	-------------------	--------------------	---------------------------------

Parts List	Item	Part Name	QTY	Description	Item	Part Name	QTY	Description
	1	Billet Grille	1	Aluminum	3	Studs	8	6-32 × 2 1/2"
2	Kep Nuts	16	6-32	4	Washers	16		

Install Notes:
 Overlay
 Replacement
 Drill
 Cut

Step	Description	illustration
1	Identify the grille & hardware with parts list.	
2	Remove seven plastic fasteners along the top front side of the grille; use a small screwdriver to pull the center from each fastener (1). Remove twelve 10mm bolts securing the radiator cover. Two of these are located on each side of the vehicle under the hood seal in the corner (2). Remove the bracket on each side. Un pop the bumper cover from the fender. Remove two 10mm bolts securing the coolant overflow tank; slide it back for clearance (3). Next, push the radiator cover back; depress the clips securing a wiring harness to the cover, unclip the hood latch cord and remove cover (3). Remove five 10mm nuts behind the grille. Depress the molded clips retaining the grille and remove from the front.	
3	Center the insert into the opening. The mounting tabs align with the factory mounting holes. Slide the mounting brackets into the mounting holes. Thread a stud in each nut welded to the grille.	
4	On each of the studs; place a washer and kep nut (4). Making sure that the grille is centered, tighten down the hardware.	
5	Re-install the wiring harness and radiator cover. Secure the coolant overflow tank.	
6	Installation completed!!!	N/A

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!