

Grille Installation Instruction

Rev. 190401

Part#	GR14GED06T/H Application F				Fo	or 2002-2004 Nissan Altima							
Parts L	ist	Item	Part Nan	ne	QTY		scriptio		Item	Part N	ame	QTY	Description
		1	Mesh Grille		1 5	Stainl	ess Stee	1					
Install Notes: Overlay × Replacement							$\sqrt{}$	Drill	ı 🗼	c	Cut	×	
Step			Descript		illustration								
1	Identify the grille with parts list.												
2	Open the hood and remove the four black plastic rivets that secure the top of the grille shell.						To remove the plastic rivets, use a flat head screwdriver pry up on the center, then lift out the whole rivet.						
3	Pull back the top of the grille shell and locate the two lower corner clips. Release these clips by squeezing the top and bottom tabs together and pull the grille shell forward. Once the corners are released, carefully pull the grille shell off the vehicle.					ips. top the are	Side View						
4	From the back of the grille shell, use a phillips head screwdriver to remove the emblem. Use the screws you just removed to attach the stock emblem to the new billet grille.						Side View	Stock	Grille	Stock Emblem			

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!



Grille Installation Instruction

Rev. 190401

Part#	GR14GED06T/H	Application	For 2002-2004 Nissan Altima				
5	Place the bottom of the into place first. Once the are in place, slide the secure with two of the that were removed in other two plastic rivets holes.	e bottom four ta top into place a four plastic rive step 2. Place t	os and dets ne				
6	Make sure everything is secure and close the hood. Enjoy the award-winning product that you have just installed!						

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!