


Part#	GR14GED11T&H	Application	For 2005-2006 Nissan Altima All Models
-------	--------------	-------------	--

Parts List	Item	Part Name	QTY	Description	Item	Part Name	QTY	Description
	1	Mesh Grille	1	Stainless steel				

Install Notes: Overlay Replacement Drill Cut

Step	Description	illustration
1	Identify the grille & hardware with parts list.	
2	Open the hood. Remove the plastic rivets that are on the stock grille shell. To remove the rivets, pry up the center 1/2" using a flat head screwdriver, then pull the rivet out completely. Save all 4 rivets for installation.	
3	Once all the black plastic rivets are removed, reach down behind the grille shell and pry the 4 clips loose. Now gently remove the stock grille shell.	
4	Align the grille with the stock grille shell opening. Set the grille into place, bottom first. Slide the grille mounting tabs into the stock mounting brackets. Make sure that all the mounting tabs slip into place.	
5	Line up the rivet hole on the top brace with the rivet hole on the vehicle. Using the stock plastic rivets, snap the grille into place.	
6	(Optional) To remove the logo, use a flat head screwdriver to pry loose the two mounting clips that hold the logo to the grille shell.	
7	Make sure the grille is centered and tighten the fasteners, but do not over-tighten.	
9	Installation completed.	

The instruction here is for your reference only. You may need to bend the grille a little bit to adjust to fit. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!