




Grille Installation Instruction

Rev. 180801

Part#	GR14GEF02T/H	Application	For 2003-2007 Infiniti G35 Coupe
-------	---------------------	-------------	---

Parts List	Item	Part Name	QTY	Description	Item	Part Name	QTY	Description
	1	Mesh Grille	1	Stainless steel	4	Top Mounting Plate	1	
	2	Flat Washers	6	6#	5	Mounting Brackets w / Clips	2	
	3	Keq Nuts	6	6-32				

Install Notes: Overlay Replacement Drill Cut

Step	Description	illustration
1	Identify the grille & hardware with parts list.	
2	Optional (for vehicles with black plastic cover under hood), pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. If you are still unable to access the rear, remove the grille shell and reattach after installation.	
3	Remove the factory grille shell; use a small screwdriver to pull the center from each fastener. Two of the fasteners will be re-used; do not discard the fasteners. Next, lightly pull the top of the grille assembly forward. There is one clip in each corner of the factory grille. Depress each clip by hand or with a screwdriver. Use your fingers to depress the molded clips along the bottom of the grille. The grille can now be removed.	
4	Attach the mounting brackets with the clips to the grille. Attach them to the studs along the bottom; secure them using the keq nuts and washers. Attach the top mounting plate to the grille. The holes in plate align to the factory mounting holes.	
5	Center the grille into the opening. The lower mounting brackets align into the factory holes. Snap the brackets in place. Use the factory fasteners to attach the upper mounting plate. It may be necessary to slightly bend the brackets and (or) mounting plate tabs so the grille aligns correctly.	
6	Make sure the grille is centered and tighten the hardware.	
7	Reinstall the black plastic cover which was removed in step 2.	
8	Installation completed.	

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!