

## Grille Installation Instruction

Rev. 150116

Part Name QTY

Part# GR14GEF07T Application 03~06 Infiniti FX35/ FX45 – Low Bumper Stainless Steel Mesh Grille

Part Name QTY Description Item

		Item	Par	t Name	e QTY	De	scrip	tion	Iten	า	F	art Na	me	QTY	Description
Parts List		1	Mesh Grille		1	Stair	Stainless s		4	I	Nylor	n Lock N	Nuts	3	10-24
		2 Studs		3	3 10-24×2		,	5	5 'J'		Hooks		3		
Install Notes: Overlay  Replacement ×								orill [	×		Cut	×			
Step	Description							illustration							
1	Identify the grille & hardware with parts list.														
2	Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell.														
3	Test fit the billet in place; the flat aluminum spacer welded to the grille rest on the bottom. Thread the studs into the lower mounting holes. A small amount of liquid thread lock may be applied to the threads. BE SURE NOT TO OVER-TIGHTEN THE STUDS (Over-tightening can cause dimpling to the face of the billets)														
4	Install a J hook and nylon lock nut onto each stud. Center the grille into the opening and wrap the J hooks around the rear of the bumper opening. Tighten the hardware until the grille is held in place.							N/A							
5	Make sure the grille is centered and tighten the fasteners.but do not over-tighten.						N/A								
6		nstall th tep 2.	e black <sub>l</sub>	plastic c	over which	was rem	noved	N/A							
7	Inst	allation	complet	ed!!!				N/A							

The instruction here is for your reference only. You may need to bend the grille a little bit to adjust to fit. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!