

Τ

Part#	GR14GEF11S			Application		03~0	6 In	finit	i FX3	85/	FX45 - S	tainl	ess Ste	el Mesh Grille		
		Item	Par	t Nai	me	QTY	QTY Descrip		tion	on Item		Part Name		QTY	Description	
Parts L	ict	1	Mesh G	irille		1	Stainless s		eel	4	S	Studs		2	6#-32×1 1/2″	
T arts L	.131	2	Washers			7				5	T	Top Mounting Plate				
	3 Flange Nuts 7						6-32	j-32								
Install Notes: Overlay $\boxed{\times}$ Replacement $\boxed{}$								\checkmark	C	orill	×	Cut	×			
Step	Description								illustration							
1	lde	Identify the grille & hardware with parts list.														
2	Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell.								N/A							
3	Remove the factory grille; use a small screwdriver to remove the center from the four fasteners along the top.There is one fastener securing the bumper next to the grille; use a slotted screwdriver to pop the center and remove.The fasteners will be re- used; do not discard,. Next, lightly pull the top of the grille assembly forward. Use your fingers to depress the remaining clips behind the grille. The grille can now be removed.								N/A							
4	Atta	The new grille uses a mounting plate along the top. Attach the mounting plate to the grille using the nuts and washers to secure the plate.														
5	Test fit the grille to make sure that it fits in the shell properly. Make sure the grille is centered.								N/A							
6	Fro	Thread a screw in each nut welded to the grille. From the rear, place a bracket on each screw.Then thread a nut and a washer on each screw.														
7		Make sure the billet grille is centered and tighten the fasteners.but do not over-tighten.														
8	Reinstall the black plastic cover which was removed in step 2.								N/A							
9	Inst	Installation completed!!!														
	1															

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during

Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.

We are not responsible for any damage caused by the installation. Thank you for choosing our product!