

Grille Installation Instruction

Part#	(GR14	GFC83T/H	Application For 2012-2019 NISSAN NV 2500				2500/35	600 Main Upper		
Parts List		Item	Part Name	QTY	Des	scription	Item	Part Name	QTY	Description	
		1	Mesh Grille	3	Stainl	ess Steel	3	Studs	10	0.138-32 X 1.5"	
		2	Flange Hex N	uts 10	0.138	-32	4	Flat tabs	10		
Install Notes: Overlay \checkmark Replacement \times							ill >	Cut	×		
Step	Description						illustration				
1	Identify the grille & hardware with parts list.								5		
2	Optional (for vehicles with black plastic cover under hood), Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. If you are still unable to access the rear, remove the grille shell and reattach after installation.										
3	Thread a stud in each nut welded to the grille. Center the grille into the opening of the factory grille shell. Be sure the studs are through the OEM grille shell.										
4	Secure the grille using the flat tab and flange hex nut from the back side of the OEM grille shell. (10) 1.5" Studs(10) Flat tabs(10) Flat tabs(10) Flange Hex Nuts										
5	Make sure the grille is centered and tighten the fasteners. But not over-tighten.										
6	Reinstall the black plastic cover which was removed in step 2.										
7	Installation completed!!!]D		

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!