

Item

**Part Name** 

## Grille Installation Instruction

Rev. 150116

Description

Part# | GR14GFD64T | Application | O7~08 Nissan Maxima – Low Bumper Stainless Steel | Mesh Grille

Description Item

**Part Name** 

		цеш	Part Nan	ie Qii	Desci	ipuon	пеш	Partina	me	QII	Description	
Parts Li	iet	1	Mesh Grille	1	1 Stainless st		4	Nylon Lock Nu	uts	5	6-32	
raits Li	2		L Brackets	5			5	Washers		5		
		3 Studs		5	6-32×2	"						
Install Notes: Overlay  Replacement ×						<u> </u>	Orill	× Cut	×			
Step	Description						illustration					
1	Identify the grille & hardware with parts list.											
2	Open the hood and remove the factory plastic radiator cover and grille assembly. Now remove the factory grille shell; use a small screwdriver to pull the center from each fastener. Do not discard the fasteners. Release the four molded clips along the bottom of the grille.											
3	Center the grille in place. Thread a stud in each nut welded to the grille. From the rear, place a bracket on each stud. Use a washer and nut to secure the grille. Make sure the brackets wrap around the edge of the bumper opening.											
4	Secure billet grille using the nuts from the back side of the OEM grille shell.					le N/A	N/A					
5	Make sure the grille is centered and tighten the fasteners.but do not over-tighten.					N/A	N/A					
6	Reinstall the black plastic cover which was removed in step 2.						N/A					
7	Installation completed!!!											

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.

Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.

We are not responsible for any damage caused by the installation. Thank you for choosing our product!