
## PN: GR14GFE83T 2007 Infiniti G35 Sedan Upper Class Mesh Grille – Polished Stainless Steel

Hardware


4 -- Plastic Retainers

NOTE: Instruction for billet grille also applies to stainless steel grille.

- (1) Remove six plastic fasteners along the top of the grille; use a small screwdriver to pull the center from each fastener (1). Remove five 10mm bolts securing the radiator cover. Remove two 10mm bolts securing the coolant overflow tank; slide it back for clearance (2). Next, push the radiator cover back; depress the clips securing a wiring harness to the cover, remove (2). Remove five 10mm nuts behind the grille. Depress the molded clips retaining the grille and remove from the front. If installing a bumper grille, install the bumper billet and then go to step 2 below.
- (2) Center the billet insert into the opening. The mounting tabs align with the factory mounting holes. Slide the mounting brackets into the mounting holes. Use the plastic retainers to retain the mounting tabs from behind the bumper; press the retainers into the mounting tab holes (3).
- (3) Re-install the wiring harness and radiator cover. Secure the coolant overflow tank.









The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!