


Part#	GR14GFH37T/H	Application	For 2006-2008 Infiniti FX-Series
-------	--------------	-------------	----------------------------------

Parts List	Item	Part Name	QTY	Description	Item	Part Name	QTY	Description
	1	Mesh Grille	1	Stainless steel	4	Nut	3	6-32
	2	Washer	3		5	Stud	2	6-32×2.5"
	3	Stud	1	6-32×1"	6	L Brackets	3	

Install Notes: Overlay Replacement Drill Cut

Step	Description	illustration
1	Identify the grille & hardware with parts list.	
2	The factory grille must be removed to install bumper grille, use a small screwdriver to remove the center from the fasteners along the top. There is one fastener securing the bumper next to the grille; use a slotted screwdriver to pop the center and remove. The fasteners will be re-used; do not discard. Next, lightly pull the top of the grille assembly forward. Use your fingers to depress the remaining clips behind the grille. The grille can now be removed.	
3	Remove the chrome molding in the bumper opening. Three 10mm nuts retain the strip from behind the bumper; remove these nuts. The chrome molding is also retained with four pressure clips that snap into the bumper. Use a slotted screwdriver to pry the molding forward to release these clips if needed.	
4	Center the grille in place. Thread a stud in each nut welded to the grille. Install the supplied washers, L brackets and 6-32 nuts onto the studs and tighten. If needed, loosen the hardware and adjust.	
5	Installation completed!!!	

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!