



# Grille Installation Instruction

Rev. 200801

Part#	GR14GGH99T	Application	2007-2008 Nissan Maxima
-------	------------	-------------	-------------------------

Parts List	Item	Part Name	QTY	Description	Item	Part Name	QTY	Description
	1	Mesh Grille	2	Stainless steel	5	Mounting Brackets w / Clips	2	
	2	Nylon Lock Nuts	10	6-32	6	Top Mounting Plate	1	
	3	Flat Washers	10	#6	7	Studs	5	6-32×2"
	4	L Brackets	5					

Install Notes: Overlay  Replacement  Drill  Cut

Step	Description	illustration
1	Identify the grille & hardware with parts list.	
2	Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell.	
3	Start with the bumper grille. Remove the factory grille shell; use a small screwdriver to pull the center from each fastener. Do not discard the fasteners. Release the four molded clips along the bottom of the grille.	
4	Center the grille in place. Thread a stud in each nut welded to the grille. From the rear, place a bracket on each stud. Use a washer and nut to secure the grille. Make sure the brackets wrap around the edge of the bumper opening.	
5	Continue to the main grille. Install the top mounting plate to the grille using the nuts and washers. Use the remaining nuts and washers to attach the mounting brackets to the bottom. Point the mounting clips towards the top.	
6	The top plate and mounting brackets align to the factory holes. Center the grille in place. Slide the lower brackets in place. The grille should rest flush to the bumper cover opening. It may be necessary to slightly bend the lower brackets so the grille sits flush to the bumper cover. Remove the grille and adjust if needed. Use the factory fasteners to secure the top mounting plate. Re-install the radiator cover using the factory fasteners.	
7	Reinstall the black plastic cover which was removed in step 2.	
8	Installation completed!!!	

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!