Grille Installation Instruction

Part#	art# GR 2		R14HEA16 A/H		Ap	Application		For 1995-1997 Nissan Hardbody Pickup					
		ltem	Part Name			QTY Desc		cription	Item	Part Name	QTY	Description	
Parts Li	st	1	Billet Grille			3	Aluminu	um	3	Kep Nuts	12	8-32	
		2	Slotted Head Screws			12	8-32×′	1/2″					
Install Notes: Overlay \times Replacement \checkmark Drill \checkmark Cut \checkmark													
Step	tep Description								illustration				
1	Identify the grille & hardware with parts list.												
2	Remove the factory grille shell and save all hardware.												
3	Tape off the face off the factory grille shell to protect against scratches.												
4	Using an air saw or die grinder carefully cut out the center sections of each of the three openings. Only removing the cross bar or honeycomb sections.												
5	Carefully smooth out the rough areas that remain by using a file.												
6	Fit each billet insert into the appropriate factory grille shell opening. When the billet insert are sitting flush and center, mark and drill the mounting holes.												
7	Secure the billet inserts to the factory grille shell using the #8 screws and nut.												
8	Make sure the grille is centered and tighten the fasteners.												
9	Install the factory grille shell with the new billet inserts back on to the vehicle using the hardware saved from Step 2.												
10	Installation completed!!! N/A												

The instruction here is for your reference only. You may need to bend the grille a little bit to adjust to fit. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!