

Grille Installation Instruction

Rev. 190801

Part#	GR14HEA17A/H	Application	For 1995-1997 Nissan Hardbody Pickup
-------	--------------	-------------	--------------------------------------

		Item	Part Nam	e QTY	Descr	iption	Item	Part Na	ıme	QTY	Description	
Parts Li	ist	1	Billet Grille	2	Aluminun	า	3	Washers		4	1/4"	
		2	2 Hex Bolts		4 1/4" -20×3/4"		4	Nuts		4	1/4" -20	
Install Notes: Overlay $\sqrt{}$ Replacement \times					Dri	II ×	Cut	×				
Step	Description						illustration					
1	Identify the grille & hardware with parts list.						d b					
2	Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell.											
3	Remove bumper. Remove stock blinker lights.											
4	Pre-fit grille into bumper.Use bolts, nuts and washers provided to install grille to pre-exsting holes on the bumper.						Boits provided Washer provided Nut provided Tab on billet grille Front of Bumper					
5	Center the billet grille into the opening of the factory grille shell. Secure the bolt to the threaded holes on the front of the grille. Be sure the bolts are through the OEM grille shell.											
9	belo	ow. Thi	ker light, sliding i s should be a tig e necessary.			, , , , , , , , , , , , , , , , , , ,						
7	Make sure the billet grille is centered and tighten the fasteners, but do not over-tighten.											
8	Reinstall the black plastic cover which was removed in step 2-3.											
9	Installation completed!!!											

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.

Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.

We are not responsible for any damage caused by the installation. Thank you for choosing our product!