

PATENT PRODUCT

Grille Installation Instruction

Rev. 180401

Part# **Application** GR14HEB18C/J For 2009-2014 Nissan Maxima **Part Name Item Part Name QTY Description** Item **QTY** Description **Parts List** Billet Grille 1 Stainless steel 2 Push In Clips 4 Install Notes: Overlay Replacement Drill Cut Step **Description** illustration Identify the grille & hardware with parts list. 1 Open the hood and remove the factory plastic radiator cover. Remove the factory air intake plate on the driver side of the vehicle. Now remove the 2 N/A factory grille shell; release the molded clips along the perimeter of the grille. If installing a bumper insert. Locate the new grille insert. Place the grille into the factory opening. The welded tabs will fit into the 3 N/A factory mounting holes . Place the provided clips into each of the tabs. Make sure the billet grille is centered and tighten 4 N/A the fasteners.but do not over-tighten. Reinstall the black plastic cover which was removed 5 N/A in step 2. 6 N/A Installation completed!!!

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.

Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.

We are not responsible for any damage caused by the installation. Thank you for choosing our product!