Grille Installation Instruction

APS AUTO PARTS SPECIALIST INC.

Rev. 190601

Part#	GR14HEF02A/H	Application	For 2003-2007 Infiniti G35 Coupe

Parts List	Item	Part Name	QTY	Description	Item	Part Name	QTY	Description
	1	Billet Grille	1	Aluminum	4	Washers	2	1/4″
	2	Hex Bolts	2	1/4″-20×3/4″	5	Lock Washers	2	
	3	Nuts	2	1/4″-20				

Install Notes: Overlay [×]   Replacement [√]   Drill [×]   Cut [×]

Step	Description	illustration
1	Identify the grille & hardware with parts list.	
2	Remove the factory grille shell; use a small screwdriver to put the center from each fastener; Two of the fasteners will be re-used; do not discard the fasteners . Next, lightly pull the top of the grille assembly forward. There is one clip in each corner of the factory grille .depress each clip by hand or with a screwdriver .Use your fingers to depress the molded clips along the bottom of the grille. The grille can now be removed.	
3	Center the billet insert into the opening. The lower mounting tabs align into the factory holes .Use a 1/4″bolt ,nut and washer to secure the lower tabs .Use the factory fasteners to attach the upper mounting brackets. These brackets align to the factory holes also .It may be necessary to slightly bend the upper brackets so they align correctly.	
4	Close the hood and check the alignment of the billet insert .If necessary, remove and adjust the brackets.	
5	Make sure the billet grille is centered and tighten the fasteners, but do not over-tighten.	
6	Reinstall the black plastic cover which was removed in step 2.	
7	Installation completed!!!	

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.
Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.
We are not responsible for any damage caused by the installation. Thank you for choosing our product!