

7

Installation completed.

PATENT PRODUCT Grille Installation Instruction

Rev. 20210501

Part#	N85602C&J&S	Application	For 2003-2007 Infiniti G35 Coupe
-------	-------------	-------------	----------------------------------

	Ite	m	Part Name	QTY	Description		Item	Part Name	QTY	Description		
Parts Li	#		Billet Grille	1	Stainless Steel		#4	Washers	2	1/4"		
Parts Li	#2	2	Hex Bolts	2	1/4"-20×3/4"		#5	Lock Washers	2			
	#3	3	Nuts	2	1/4"-20							
Install Notes: Overlay Replacement ✓ Drill × Cut ×												
Step	Description					illustration						
1	Identify the grille & hardware with parts list.											
2	Remove the factory grille shell; use a small screwdriver to put the center from each fastener; Two of the fasteners will be reused; do not discard the fasteners. Next, lightly pull the top of the grille assembly forward. There is one clip in each corner of the factory grille. Depress each clip by hand or with a screwdriver. Use your fingers to depress the molded clips along the bottom of the grille. The grille can now be removed.											
3	Center the billet insert into the opening. The lower mounting tabs align into the factory holes. Use a 1/4 "bolt, nut and washer to secure the lower tabs. Use the factory fasteners to attach the upper mounting brackets. These brackets align to the factory holes also. It may be necessary to slightly bend the upper brackets so they align correctly.											
4	Close the hood and check the alignment of the billet insert. If necessary, remove and adjust the brackets.											
5	Make sure the insert is centered and tighten the hardware.											
6	Reinstall the plastic shroud with the fasteners removed in Step 2 .											

The instruction here is for your reference only. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!