



Grille Installation Instruction

Rev. 121001

Part#	GR14HF157A	Application	2008-2010 Infiniti M35/45 Main Upper
-------	------------	-------------	--------------------------------------

Parts List	Item	Part Name	QTY	Description	Item	Part Name	QTY	Description
	1	Billet Grille insert	1	16 Billets	3	Nut	4	6-32
	2	Screw	4	6-32x1 1/2"	4	Washer	4	/

Install Notes: Overlay Replacement Drill Cut

Step	Description	illustration
1	Identify the grille & hardware with parts list.	N/A
2	Remove the factory grille shell;use a small screwdriver to pull the center from four fasteners along the top.The fasteners will be re-used;do not discard.Lightly pull the top of the grille assembly forward. Use a screwdriver to depress two clips(one in each corner;top).Depress the molded clips along the bottom.Use a slotted screwdriver to pry two remaining detents (one in each corner;bottom).The grille can now be removed.If installing a bumper billet,install the bumper billet and then go to step 3 below.	N/A
3	Center the billet insert into the opening .While holding the grille into place; place a screw through the grille bracket and factory grille backing. From the backside of the grille;place a washer and lock nut on each screw. Repeat this on the remaining lower screws.	N/A
4	The upper mounting tabs align to the factory mounting holes.It may be necessary to slightly bend the brackets so they align properly.Use the factory fasteners to secure the billet on top.	N/A
5	Tighten all the hardware.Carefully check the hood clearance to the billet grille.Re-move the billet and adjust the brackets if needed.	N/A
6	Installation completed!!!	N/A

The instruction here is for your reference only. You may need to bend the grille a little bit to adjust to fit. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!