

PATENT PRODUCT

Grille Installation Instruction

Rev. 200601

Part#	GR14HGG74S App		Applica	cation For 2009		0-2014 Nissan Maxima					
		ltem	Part Name		QTY	Y Description		ltem	Part Name	QTY	Description
Parts Li	iot i	1	Billet Grille		2	Stainless steel		4	Push In Clips	4	
Faits L	2		J Hooks		2	2.5″		5	J Hooks	2	1 ″
		3	U Nuts	s 4		#8		6	Screws (#6 Head)	4	#8×1 1/4″
Install N	lote	es: Ov	erlay	× Re	eplacer	nent 🗸	D	orill >	Cut ×		
Step	Description						illustration				
1	Identify the grille & hardware with parts list.										
2	Start from the main upper piece. Open the hood and remove the factory plastic radiator cover. Remove the factory air intake plate on the driver side of the vehicle. Now remove the factory grille shell; release the molded clips along the perimeter of the grille. If installing a bumper insert.										
3	Locate the new grille insert. Place the grille into the factory opening. The welded tabs will fit into the factory mounting holes . Place the provided clips into each of the tabs.										
4	Now move on to the bottom piece. Slide the u-nuts onto J hooks. Insert the screws into the tabs on the billet. Start to thread the shorter J hooks onto the top screws (1). Start to thread the longer J hooks onto the lower screws (2). Center the grille in place. Wrap the hooks around plastic bars in the openings.										
5	Make sure the billet grille is centered and tighten the fasteners, but do not over-tighten. Reinstall the black plastic cover which was removed in step 2.										
6	Installation completed.										

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!