



Part#	GR14HGI81J	Application	2004-2006 Nissan Maxima
--------------	------------	--------------------	-------------------------

Parts List	Item	Part Name	QTY	Description	Item	Part Name	QTY	Description
	1	Billet Grille	2	Stainless steel	6	Lock Washers	2	1/4"
	2	Hex Bolts	2	1/4"-20x3/4 "	7	Screws	4	8#x3/4"
	3	Nuts	2	1/4"-20	8	Flat Nuts	4	8#
	4	Flat Washers	2	1/4"	9	U-Clip Nut	4	8#
	5	'J' Hooks	4		10	Truss Socket Tapping Screws	4	8x1"

Install Notes: Overlay Replacement Drill Cut

Step	Description	illustration
1	Identify the grille & hardware with parts list.	
2	Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell.	
3	Start with the upper section. Center the billet insert in the opening. The top mounting tabs should align with factory mounting holes (it may be necessary to slightly bend the brackets). Hold the billet insert firmly in place. Make sure it is centered. Mark the holes in the lower mounting tabs to the opening. Remove the billet insert and drill a 1/8" hole at each mark. Re-center the insert in the opening and use the #8 screws and flat nuts to fasten the lower mounting tabs. Attach the top mounting brackets using the bolts, nuts and washers.	
4	Center the plastic header panel over the stock location. Drill a 1/4" hole through the two bumps on top of the header panel. Secure it using two of the factory plastic fasteners.	
5	Make sure the billet grille is centered and tighten the fasteners, but do not over-tighten.	
6	Move on to the lower section. Center the billet grille into the opening of the factory grille shell. Secure the screw to the threaded holes on the front of the grille. Be sure the screws are through the OEM grille shell.	
7	Secure billet grille using the u-clip nuts and J hooks from the back side of the OEM grille shell.	

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!



Grille Installation Instruction

Rev. 200801

Part#	GR14HGI81J	Application	2004-2006 Nissan Maxima
8	Make sure the billet grille is centered and tighten the fasteners.		
9	Reinstall the black plastic cover which was removed in step 2.		
10	Installation completed!!!		

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!