AU	Grille Installation Instru								ruction		Rev. 180601	
Part#	GR18FFC80 A/H Application For 2015-2018 Chrysler 300C/300S WITH ADAPTOR CON Lower Bumper									DAPTOR CONTROL		
		ltem	Part Nan	ne	QTY	Descri	otion	Item	Part Name	QTY	Description	
Parts L	ist	1	Billet Grille		2	Aluminum		3	Screws	4	6-32X1.5"	
		2	Toggle Nuts		4	6-32						
Install Notes: Overlay 🗸 Replacement 🗵									√ Cut	×		
Step	Description						illustration					
1	Identify the grille & hardware with parts list.											
2	Optional (for vehicles with black plastic cover under hood), Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. If you are still unable to access the rear, remove the grille shell and reattach after installation.											
3		Center the grille into the opening of the factory grille shell. Secure the screw to the threaded holes on the front of the grille.Be sure the screws are through the OEM grille shell. You need mark and drill 2 holes.										
4	fror	Secure the grille using the toggle nut from the back side of the OEM grille shell.										
5	Ma	Make sure the billet grille is centered and tighten the fasteners.										
6	Rei	Reinstall the black plastic cover which was removed in step 2.										
7	Installation completed!!!							6		0		

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!