

## Grille Installation Instruction

Rev. 180501

Part#	G	R18G	GFC78S/K	Application	on For 20	015-2018 Chrysler 300C/300S Main Upper					
		Item	Part Nam	e QTY	Descrip	otion	Item	Part Name	QTY	Description	
Parts L	ist	1	Mesh Grille	1	Stainless	steel	3	Flat Tab	6		
		2	Hex Flange I	Nut 6	0.138-32L	INC	4	Studs	6	0.138-32UNCX1.5"	
Install Notes: Overlay VReplacement XDrill XCut X											
Step	Description					illustration					
1	Identify the grille & hardware with parts list.										
2	Optional (for vehicles with black plastic cover under hood), Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. If you are still unable to access the rear, remove the grille shell and reattach after installation.										
3	Thread a stud in each nut welded to the grille.Center the grille into the opening of the factory grille shell. Be sure the studs are through the OEM grille shell.										
4	Secure the grille using the flat tab and hex flange nut from the back side of the OEM grille shell.										
5	Mal	Make sure the billet grille is centered and tighten the fasteners.									
6	Rei	Reinstall the black plastic cover which was removed in step 2.									
7	Inst	allation	completed!!!						alakir centralis		

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.

Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!