

Item

Part Name

Grille Installation Instruction

Rev. 150116

QTY

Description

Part#	GR18GFE27H	Applic ation	07~09 Chrysler Aspen – Main Upper Stainless Steel Mesh Grille
-------	------------	--------------	--

Item

Description

QTY

Part Name

		1	Mesh Grille	1	Stainless steel	5	L Brackets	4		
Parts List		2			6-32×2 1/2"	6	Nylon Lock Nuts	8	6-32	
		3 Flat Washers		4		7	Phillips Screws	4	#8 ×3/4"	
		4	Flat Nuts	4	8#					
Install N	Note	s: O\	verlay × F	Replacen	nent	Drill	Prill √ Cut √			
Step	Description					illustration				
1	lder	ntify the	e grille & hardware v	vith parts li	st.					
2	Open the hood and remove six plastic fasteners securing the radiator cover. Remove two 13mm bolts along the top of the grille. Use needle nose pliers to release four plastic clips (1) along the bottom of the grille (from behind).									
3	Apply masking tape to the chrome edge around the factory grille. Cut the center cross bars from the grille; cut approximately 1/2 " inside the outside border (2). Remove the center bars from the factory grille (3).									
4	end allov ope	s (the w the f ning (4 sh grille	grinder to file 1/16 " four cut bars next frame on the new m l). File material in ir e in place. This w	to the he esh grille ntervals; w	adlights). This wi to sit flush into the hile test fitting the	II e e				
5	Center the grille in place. Install an L bracket, washer and nut on each stud. Wrap the L brackets around the edge of the grille (5). Adjust the grille to the desired fit; drill a 1/8" hole aligned with the mounting tabs (6). Use the #8 screw and flat nuts to secure the mounting tabs.									
6	Make sure the billet grille is centered and tighten the fasteners.but do not over-tighten.					N/A				
7	Re-install the grille assembly and radiator cover.					N/A				
8	Installation completed!!!					N/A				

The instruction here is for your reference only. You may need to bend the grille a little bit to adjust to fit. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!