



Part#	GR20FED50A/H	Application	For 2006-2008 Toyota Yaris Hatchback
-------	---------------------	-------------	---

Parts List	Item	Part Name	QTY	Description	Item	Part Name	QTY	Description
	1	Billet Grille	1	Aluminum	4	Nylon Lock Nuts	2	6-32
	2	U- Clip Nuts	2	8#	5	6 Head Screws	2	1 1/4" #8
	3	Machine Screws	2	1 3/4"	6	Flange Brackets	4	2"

Install Notes: Overlay Replacement Drill Cut

Step	Description	illustration
1	Identify the grille & hardware with parts list.	
2	Remove the 10mm bolts securing the lower motor skid plate to access the rear of the grille.	
3	Place the provided U Nuts onto two of the flange brackets. Place the upper grille in place. Place the #8 6 head screws into the two outside welded grille brackets. While holding the grille; place the two brackets on the outside screws (1)	
4	Tighten till snug. Place the machine screw into the center bracket. Place a flange bracket and nylon lock nut onto the machine screw and tighten (2). With the grille centered; tighten all the hardware.	
5	Re-install the lower skid plate assembly onto the vehicle using the factory hardware.	
6	Installation completed!!!	



The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.
Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!