

Grille Installation Instruction

Rev. 180501

Part#		GR20FFE53A/H		Application		For 2008-2017 Toyota Sequoia				
		Item	Part Name	QTY	Desc	ription	Item	Part Name	QTY	Description
Parts L	-4	1	1 Billet Grille		Aluminum		4	2-Hole Tabs	4	
Parts Li	δ ι	2	Flat Tabs	4			5	Truss Head Tapping Screws	8	8×3″
		3	U- Clip Nuts	8 8#						
Install Notes: Overlay Replacement										
Step	Description					illustration				
1	Identify the grille & hardware with parts list.									
2	Optional (for vehicles with black plastic cover under hood), Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. If you are still unable to access the rear, remove the grille shell and reattach after installation.									
3	Place one screw through each of the welded tabs on the billet grille.									
4	Place a U-clip nut over the holes on the flat tabs.									
5	Place a tab behind the grille shell in line with were the screw comes through. Tighten each of the screws evenly so as not to put the grille in a bind and not to make it go off center.									
6	Make sure the billet grille is centered and tighten the fasteners.									
7	Reinstall the black plastic cover which was removed in step 2.									
8	Installation completed!!!									

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.

Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.

We are not responsible for any damage caused by the installation. Thank you for choosing our product!