



# PATENT PRODUCT Grille Installation Instruction

Rev. 20201101

<b>Part#</b>	T66553C&J&S	<b>Application</b>	For 2008-2017 Toyota Sequoia
--------------	-------------	--------------------	------------------------------

	Item	Part Name	QTY	Description	Item	Part Name	QTY	Description
<b>Parts List</b>	#1	Billet Grille	1	Stainless Steel	#4	2-Hole Tabs	4	
	#2	Flat Tabs	4		#5	Truss Head Tapping Screws	8	8x3"
	#3	U-Clip Nuts	8	8#				

**Install Notes:** Overlay  Replacement  Drill  Cut

Step	Description	illustration
1	Identify the grille & hardware with parts list.	
2	Optional: pop hood, remove the black plastic cover (on top of OEM grille) from vehicle. If you are still unable to access the rear, remove the grille shell according to factory manual.	
3	Install the U-clip nuts onto the tabs as shown.	
4	Thread a Screw in each nut welded to the grille. Secure billet grille using the U-Clip Nuts and tabs from the back side of the grille shell.	 <div style="border: 1px solid black; padding: 2px; width: fit-content; margin: 0 auto;">Top: 2-hole tab; Bottom: flat tab</div>
5	Make sure the insert is centered and tighten the hardware.	
6	Reinstall the plastic shroud with the fasteners removed in Step 2.	
7	Installation completed.	

The instruction here is for your reference only. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!