

I

Grille Installation Instruction

Τ

Part#	GR20FFF02A			Application		09~10 Toyota Corolla – Billet Grille					
		Item	Part	Name	QTY	Descrip	tion	Item	Part Name	QTY	Description
Parts L	.ist	1	Billet Gri	ille	4	Aluminum		3	Truss Head Screws	12	6-32 × 2 ″
		2 Toggle N		Nuts 12		6#					
Install Notes: Overlay \checkmark Replacement \times							C	Drill ×	Cut ×		
Step	Description						illustration				
1	Identify the grille & hardware with parts list.									N N	
2	Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell.						N/A				
3	Place screws through the welded aluminum tabs on the grille, and attach a toggle nut on the end of each bolt.										
4	Hold the billet insert up to the opening of the factory shell, make sure that it is centered in the grille shell, and push in the toggle nut past the factory grille.						N/A				
5	Turn the toggle nut so that it is vertical, and tighten. But not over-tighten!						N/A				
6	Repeat steps three and four for the remaining billet grille.						N/A				
7	To install the fog light grille, you have to drill holes on the OEM grille. Then repeat step (3) (4).						N/A				
8	Installation completed!!!							N/A			

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during

Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.

We are not responsible for any damage caused by the installation. Thank you for choosing our product!