

Grille Installation Instruction

Rev. 121010`

Part#		GR20FFI33J		Application For 2		or 2012-2	2012-2014 Toyota Camry SE					
Parts List		Item	Part Name		QTY	Description		Item	Part Name	QTY	Description	
		1	Billet Grille insert		1	1 Stainless ste		3	Toggle Nut	6	6-32	
		2	Bolt		6	6-32×1	1/2"	4	1	/	1	
Install Notes: Overlay								rill ×	Cut	×		
Step	Description							illustration				
1	Identify the grille & hardware with parts list.							7) -1) -1) -1) -1) -2 -7		-		
2	Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell.											
3	Center the billet grille into the opening of the factory grille shell. Secure the bolt to the threaded holes on the front of the grille.Be sure the bolts are through the OEM grille shell.											
4	Secure billet grille using the toggle nuts from the back side of the OEM grille shell.							6Toggle Nuts				
5	Make sure the billet grille is centered and tighten the fasteners.							N/A				
6	Reinstall the black plastic cover which was removed in step 1.						ved N/A	N/A				
7	Installation completed!!!											

The instruction here is for your reference only. You may need to bend the grille a little bit to adjust to fit. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!