

PATENT PRODUCTGrille Installation Instruction

Rev. 20201101

Part#	T75464T&H		Application		For 200	For 2007-2009 Toyota Tundra						
		Item Part		Name QTY		Desc	Description		Part Name	QTY	Description	
Parts Li	ist	1#	Mesh Grille		1	Stainless Steel		3#	Flat Tabs	11		
		2#	Studs		11	10-24×3″		4#	K-Lock Nuts	11	10-24	
Install N	Note	es: O	verlay	$\sqrt{}$	Repla	cement	× Dril	I ×	Cut ×			
Step	Description							illustration				
1	Ider	Identify the grille & hardware with parts list.										
2	Optional: pop hood, remove the black plastic cover (on top of OEM grille) from vehicle. If you are still unable to access the rear, remove the grille shell according to factory manual.											
3	Thread a Stud in each nut welded to the grille. From the rear, place a Flat Tab on each Stud. Now thread a K-Lock Nut on each Stud.											
4	Mal	Make sure the insert is centered and tighten the hardware.										
5	Reinstall the plastic shroud with the fasteners removed in Step 2.											
6	Inst	Installation completed.										

The instruction here is for your reference only. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!