

## PATENT PRODUCT Grille Installation Instruction

Rev. 20231201

Drill (1) Hole

(1) #6x1.5 Stud (2) Hex Flange Nut

(1) Flat Tab (short)

	Ite	n Pa	art Name	QTY	Description	Item	Part Name	QTY	Description	
Danta I	#1	#1 Mesh Grille		2	Stainless Steel	#4	Flat Tabs (Short)	8		
Parts L		#2 Studs		12	#6X1.5"	#5	Flat Tabs (Long)	4		
	#3	#3 Hex Flange Nuts		12	#6					
nstall l	Notes:	Overlay	√ Rep	lacem	ent × Dr	iII √	Cut ×			
Step		De	escription			illustration				
1			hardware with							
2	Optional: pop hood, remove the black plastic cover (on top of OEM grille) from vehicle. If you are still unable to access the rear, remove the grille shell according to factory manual.									
	Hold the mesh grille against the OEM grille shell, center and mark (4) holes for drilling. Remove billet grille and drill holes according to your mark.									
3	accordi	Thread a Stud in each nut welded to the grille. From the rear, place a Flat Tab on each Stud. Now thread a Hex Flange Nut on each Stud.								
4	Thread		each nut weided	to the	grino. From the roat,		Tat Tab on Gaon Glad.	Trow tillout	- a riox riango iv	

The instruction here is for your reference only. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!

(4)#6X1.5" Studs (4) Hex Flange Nuts (4) Flat tabs (long)

52411-0R020\_5582

165582

Drill (1) Hole (1) #6x1.5 Stud

(1) Hex Flange Nut

(1) Flat Tab (short)



## PATENT PRODUCT Grille Installation Instruction

Rev. 20231201

Part#	T75582T&H	Application	For 2013-2015 Toyota RAV4				
5	Make sure the insert is centered and tighten the hardware.						
6	Reinstall the plastic shroud with the fasteners removed in Step 2.						
7	Installation complet	ted.	5.582				