

Grille Installation Instruction

Rev. 190801

Part#	T85394A/H		For 1999-2002 Toyota Tundra Not For Iven Stewart
			Edition (14 Bars)

		Item	Part Name		QTY Descr		iption	Item		Part Name			QTY Description		
Parts L	ist 1		Billet Grille		1 Aluminum		ım	3	Truss Socket Tapping S			Screws	4	10×3/4″	
		2	U- Clip Nuts		4	4 10#									
Install Notes: Overlay × Replacement √ Drill √ Cut √															
Step	p Description illustration														
1	Identify the grille & hardware with parts list.														
2	Open hood and remove safety latch release lever.														
3	Take off the six nuts retaining the grille shell to the hood and remove the grille shell.														
4	Mask the outer chrome ring of the grille shell to protect it from scratches.														
5	With a hacksaw blade and handle, saw the horizontal and vertical bars out of the grille shell. Do not cut out the mount for the hood safety release handle! front side of grille cut out factory grille area, cut along dotted line										ong dotted line				
6	Center the billet grille in the grille opening. Using the holes in the 4 welded tabs as a guide, mark and drill four 3/16" holes in the grille shell.														
7	Remove the billet grille and paint the sanded area with satin black or black texture coat.						fr	sand smooth along ring and repaint with semi-gloss or flat black front side of grille retain the safety release handle mount							
8	Reinstall the billet grille in the grille shell and secure with screws and clips. Installation completed!!!							front side of grille tinnerman clip stock grille tab on end of grille							

The instruction here is for your reference only. You may need to bend the grille a little bit to adjust to fit. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!