

Grille Installation Instruction

Rev. 200801

Part#		GR	20LAB78H		Applicatio	n For	2014-2	2019 Toyota 4F	Runner No	ot For Limited Edition	
		Item	Part Name	QTY	Descrip	otion	Item	Part Name	QTY	Description	
Parts Li	ist	1	Mesh Grille	3 10	Stainless		3	Flat Tab	10		
		2	Hex Flange Nut	0.19-24UN	IC						
Install Notes: Overlay $\boxed{\hspace{1em} \sqrt{\hspace{1em}}}$ Replacement $\boxed{\hspace{1em} \times \hspace{1em}}$ Drill $\boxed{\hspace{1em} \times \hspace{1em}}$ Cut $\boxed{\hspace{1em} \times \hspace{1em}}$											
Step			Description		illustration						
1	Identify the grille & hardware with parts list.										
2	Optional (for vehicles with black plastic cover under hood), Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. If you are still unable to access the rear, remove the grille shell and reattach after installation.										
3	Start with the upper section. Center the grille into the opening of the factory grille shell. Be sure the studs are through the OEM grille shell.										
4	Secure the grille using the flat tab and hex flange nut from the back side of the OEM grille shell.										
	grille she grille and	e into th II. Be su e shell.	o the lower section. One opening of the facture the studs are through Secure the grille using and from the bacture the grille.	tory grill ough the ng the fla	e OEM at tab				O.		

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.

Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!



Grille Installation Instruction

Rev. 200801

Part#		GR20LAB78H	Application	For 2014-2019 Toyota 4Runner Not For Limited Edition					
5	Mak	Make sure the billet grille is centered and tighten the fasteners.							
6	Reinstall the black plastic cover which was removed in step 2.								
7	Insta	Installation completed!!!							

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.

Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!