



Part#	GR21FFH26 A/H	Application	For 2008-2015 Mitsubishi Lancer Without Fog Light
--------------	--------------------------	--------------------	--

Parts List	Item	Part Name	QTY	Description	Item	Part Name	QTY	Description
	1	Billet Grille	3	Aluminum	4	Truss Head Screws	4	6-32x1"
	2	Studs	4	10-24 x 1 1/4"	5	Toggle Nuts	4	6-32
	3	K-Lock Nuts	4	10#	6	Washers	4	

Install Notes: Overlay Replacement Drill Cut

Step	Description	illustration
1	Identify the grille & hardware with parts list.	

FOR CENTER BILLET GRILLE:

2	Optional: remove the plastic cover on the bottom of the OEM front bumper, which will allow access to the rear of the OEM grille	
3	Insert the screws into the weld tab hole from front side of the billet grille.	<div style="border: 1px solid black; padding: 5px; display: inline-block;"> Picture for reference only. This is not actual grille. </div>  <div style="display: flex; flex-direction: column; margin-left: 10px;"> <div style="border: 1px solid black; padding: 2px; margin-bottom: 5px;">Weld tab</div> <div style="border: 1px solid black; padding: 2px; margin-bottom: 5px;">Screw</div> <div style="border: 1px solid black; padding: 2px;">Toggle nut</div> </div>
4	Center the billet grille onto the OEM grille. Press & insert the toggle nuts on to the rear of the OEM grille through the gap between the horizontal bars.	
5	Secure the grille using the toggle nuts and screws from the front side of the billet grille with a screw driver.	

FOR BOTH SIDE BILLET GRILLE:

6	Now thread studs into the grille, center and mark holes for drilling. Remove billet grille and drill holes according to your mark. Then push the studs through the shell and center the grille into the opening. Fasten the grille use the washers and the k-lock nuts from the rear, but do not over-tighten.
7	Make sure the billet grille is centered and tighten the fasteners.
8	Installation completed!!!

The instruction here is for your reference only. You may need to bend the grille a little bit to adjust to fit. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!