

Т

Г

Grille Installation Instruction

Т

I

Part#	GR21GGB01T			1T	Application)3 Mi	Mitsubishi Eclipse – Stainless Steel Mesh Grille							
		ltem	Part	Nam	ne QTY		Descripti		on Iter		m Part Name		ame	QTY	Description	
Parts L	.ist	1				1		ess ste		3	Т	Truss Head Tapping Screws		7	8×5/8″	
		2				8				4	F	Flat Nuts		3 8#	8#	
Install Notes: Overlay \checkmark Replacement \times								×	[Drill 🗸 Cut 🗵						
Step		Description								illustration						
1	Identify the grille & hardware with parts list.															
FOR CENTER GRILLE:																
2	Start by removing the headlamp bolts there are total of three per side.								3	, F	Remove the turn signal lamp and unplug the lamp socket.					
4	The headlamp has a plastic clip on the bottom push up in order to free the headlamp.								5	; ⁽	Unplug headlamp bulb socket from the backside.					
6	With the headlamp out of the way remove the corner bolt located in the headlamp area.								7	, F	Remove the second bolt.					
7	Unplug fog lamp socket.								8	F	Remove bolts located on the top side of the bumper.					
9	Remove the front fender splash shield plastic clips located in front of the wheel.								1(Using a socket wrench remove the corner bolt behind splash shield.(Bolt is in the vertical position)					
11	Remove plastic clips located on the bottom side of the bumper cover.								12	2 E	Bumper cover can now be removed.					
13	Insert grille into bumper opening from the front side. Hold firmly in place and mark mounting tab center holes.								14	4 ^I	Using 3/16 drill bit drill for mounting screws.					
15	Mounting screw & flat nuts.								16	6 F	Fasten grille from the backside using supplied hardware.					
FOR S	SID	E GR	ILLE	S:						L						
1	Remove original vent covers and then place the grille in from the front side.								2		Hold grille firmly in place and mark the screw tab location using a sharp scribe.					
3	Using a 3/16 drill bit. Drill mounting screw hole location.								4	1	Note the drilled hole.					
5	Install "U" Nut onto mounting tab.									; F	Fasten mounting screws from the backside.					
Install	atio	on cor	nplete	ed!!!												

The instruction here is for your reference only. You may need to bend the grille a little bit to adjust to fit. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!