


<b>Part#</b>	GR25FFD53A/H	<b>Application</b>	<b>For 2006-2008 Hyundai Sonata</b>
--------------	--------------	--------------------	-------------------------------------

Parts List	Item	Part Name	QTY	Description	Item	Part Name	QTY	Description
	1	Billet Grille	3	Aluminum	4	Screws	8	8# × 2 "
	2	"K" Clip Nuts	4	8#	5	"S" Hooks	4	
	3	"U" Clip Nuts	4	8#				

**Install Notes:** Overlay  Replacement  Drill  Cut

Step	Description	illustration
1	Identify the grille & hardware with parts list.	
2	If you are unable to reach the back of the front bumper from underneath the vehicle, remove the bumper.	
3	Center and test fit the billet grille in OEM bumper.	
4	First install center billet grille, clip the "U" clip nut onto the "S" hooks. Then, place the billet grille into the bumper opening.	
5	Push the screw through the hole of the welded tabs on the back of grille. Use "S" hooks to hook the grille on to OEM bumper opening. Center the grille and tighten the screws, but not too tight.	
6	Next install the side grilles. Place right side billet grille into OEM grille shell. Mark on the grille shell according to the tab holes on the grille. Then drill 3/4" holes according to the marks. Replace the billet grille into the grille shell. Tighten each screw and "K" nut.	
7	Repeat same step for the left side grille.	
8	Installation completed.	

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!