




Grille Installation Instruction

Rev. 190601

Part#	GR25FFF86A&H	<i>Application</i>	For 2009-2010 Hyundai Sonata
--------------	-------------------------	--------------------	-------------------------------------

Parts List	Item	Part Name	QTY	Description	Item	Part Name	QTY	Description
	1	Billet Grille	1	Aluminum	3	Flat Tabs	2	
2	Screws	4	6-32×2"	4	Nylon Lock Nuts	4	6-32	

Install Notes: Overlay Replacement Drill Cut

Step	Description	illustration
1	Identify the grille & hardware with parts list.	
2	Use a lift or raise the car on a jack and use jack stands to support it. Remove the factory fasteners that retain the lower pan and remove it for lower grille hardware access.	
3	Center the billet grille into the opening of the factory grille shell. Insert a screw in each tab welded to the grille.	
4	From the rear, place a flat tab on each screw. Now thread a nut on each screw.	
5	Make sure the insert is centered and tighten the hardware.	
6	Reinstall the black plastic cover which was removed in step 2.	
7	Installation completed!!!	

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!