





Part#	<b>GR25HFF77A/H</b>	Application	<b>For 2007-2010 Hyundai Elantra Sedan</b>
-------	---------------------	-------------	--

Parts List	Item	Part Name	QTY	Description	Item	Part Name	QTY	Description
	1	Billet Grille	1	Aluminum	3	Truss Head Tapping Screws	4	10x3/4"
2	Flat Nuts	4	10#					

Install Notes: Overlay  Replacement  Drill  Cut

Step	Description	illustration
1	Identify the grille & hardware with parts list.	
2	Optional (for vehicles with black plastic cover under hood), Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. If you are still unable to access the rear, remove the grille shell and reattach after installation.	
3	Cut and remove OEM grille, then sand smooth.	
4	Hold the billet in place and mark the bracket hole to the opening.	
5	Drill a 1/8" hole at each mark. Secure the billet using the screws and nuts provided.	
6	Make sure the billet is centered and tighten the fasteners.	
7	Reinstall the black plastic cover which was removed in step 2.	
8	Installation completed!!!	

The instruction here is for your reference only. You may need to bend the grille a little bit to adjust to fit. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!