### **iBoard**<sup>®</sup>



### iBoard<sup>®</sup> by APS

### PART#: IB-171/222C&H

Tightening Torque (ft-lbs) Fastener Size Required READ INSTRUCTIONS CAREFULLY BEFORE START ING INSTALLATION. REMOVE CONTENTS FROM BOX AND 6-7 6mm Х VERIFY ALL PARTS ARE PRESENT. ASSISTANCE IS  $\sqrt{}$ 16-18 8mm **RECOMMENDED.** 10mm 31-32 Х Х 12mm 56-58 **\*ROCKER PANEL MOUNT \*NO DRILLING REQUIRED** 14mm 92-94 Х PART LIST Front **Driver Side Step Bar** Passenger Side Step Bar 1# 1# 1# 1#

# **iBoard**®



Mounting Bracket List								
ltem	QTY	Description	ltem	QTY	Description			
1#	8	Mounting Brackets						

	Hardware Package A (For Bracket Installation)									
ltem	QTY	Description	ltem	QTY	Description					
1#	16	M8X1.25-30mm Hex Bolts	3#	16	M8 Lock Washers					
2#	16	M8 Large Flat Washers								

	Hardware Package B (For Stainless Steel Step Bar Installation)								
ltem	QTY	Description	ltem	QTY	Description				
1#	16	M8X1.25-35mm Carriage Bolts	3#	16	M8 Nylon Lock Nuts				
2#	16	M8 Large Flat Washers	4#	8	Sliders (Packed with Step Bars)				
	1# 2#		3 # 4 #		4#				

## **iBoard**<sup>®</sup>




Scan for Installation Video


#### **STEP 1**


Start the installation under the driver side of the vehicle. Locate the 8 plugs along the bottom edge of the body. Mounting Brackets will bolt to the 1st, 3rd, 4th and 6th threaded mounting holes, (Fig 1-6). Remove the plastic plugs from each mounting location. Directly above each threaded insert is the top mounting location on the side of the body panel. Hold a Mounting Bracket up in place to help determine the mounting locations.

**NOTE:** Thread an M8X1.25-30mm Hex Bolt into the threaded inserts to clear paint as required.




(Fig 1) Driver Side Mounting Locations Illustrated (NOTE: Hold a Mounting Bracket up in place to help determine the mounting locations)







(Fig 3) Driver Side Front Mounting Location



(Fig 4) Driver Side 3rd Mounting Location



(Fig 5) Driver Side 4th Mounting Location




### **iBoard**<sup>®</sup>



#### **STEP 2**

Start from the front of the side. Select and bolt the Driver Front Mounting Bracket to the 1st factory threaded holes with (2) M8X1.25-30mm Hex Bolts, (2) M8 Lock Washers and (2) M8 Large Flat Washers (Fig 7). Do not fully tighten hardware at this time.

#### Note: All (8) Mounting Brackets are universal.



#### **STEP 3**

Repeat **Step 2** to install the other (3) Mounting Brackets on the remaining driver side mounting locations along the body panel.

### **STEP 4**

Once all (4) Driver mounting brackets are installed, then proceed to the Step Bar installation. (Figs 8 & 9)

- (1) Select (1) Slider and (2) M8X1.25-35mm Carriage Bolts;
- (2) Install (2) M8X1.25-35mm Carriage Bolts in (1) Slider.
- (3) Slide the Slider (with carriage bolts) to the Step Bar.
- (4) Repeat to install the other (3) sliders to the step bar.

(5) Attach the Step Bar (with the Sliders) onto the installed mounting brackets. Position the Sliders to the installed brackets. Secure the Step Bar to the installed Brackets by using (8) M8 Large Flat Washers and (8) M8 Nylon Lock Nuts and (4) Sliders, (**Fig 9**). Do not fully tighten hardware at this time.

Note: The Sliders are packed with the Step Bars.

Level and adjust the Step Bar and fully tighten all hardware.

Repeat **Steps 1-4** for the other side Step Bar installation. **The installation is completed!!!** 

#### Attention

Do periodic inspections to the installation to make sure that all hardware is secure and tight.

In order to protect your bars/boards, please use mild soap/non-abrasive products for cleaning only.

# **iBoard**®



