i Board®




iBoard[®] by APS

PART#: IB-064C&H

READ INSTRUCTIONS CAREFULLY BEFORE START ING INSTALLATION. REMOVE CONTENTS FROM BOX AND VERIFY ALL PARTS ARE PRESENT. ASSISTANCE IS RECOMMENDED.

*BODY FRAME MOUNT
*NO DRILLING REQUIRED

Fastener Size	Tightening Torque (ft-lbs)	Required
6mm	6-7	V
8mm	16-18	V
10mm	31-32	V
12mm	56-58	V
14mm	92-94	Х



Customer Support: info@iboardauto.com

1 Rev. 20230401

iBoard®



			Har	dware Package	A (For Brac	ket Ins	tallation)	
ltem	QTY	Description		Item	QTY	Description		
1#	6	M10X1.5-30mm Hex Bolts		8#	2	M8X1.25-25mm Hex Bolts		
2#	12	M10 Large Flat Washers		9#	4	M8 Large Flat W	ashers	
3#	6	M10 Lock Washers			10#	2	M8 Nylon Lock	Nuts
4#	6	M10 Hex Nuts		11#	2	M6X1-30mm He	x Bolts	
5#	2	M12X1.75-100mm Hex Bolts			12#	4	M6 Flat Washers	
6#	4	M12 Large	2 Large Flat Washers		13#	2	M6X1 Nylon Lock Nuts	
7#	2	M12 Nylon	Lock Nuts					
		#	2#	3#	4#		5#	6#
		0		0	0			0
	7#	- #	8#	9#	10#		11#	12# 13#

Hardware Package B (For Stainless Steel Step Bar Installation)						
ltem	QTY	Description		QTY	Description	
1#	8	M8X1.25-35mm Carriage Bolts	3#	8	M8 Nylon Lock Nuts	
2#	8	M8 Large Flat Washers	4#	4	Sliders (Packed with Step Bars)	
		1# 2#		3#		

2 Rev. 20230401

4#

Board®




Scan for Installation Video

STEP 1

Start installing from the passenger side front of the vehicle. Remove the passenger front body mount bolt.

STEP 2

Assemble Passenger Front Mounting Bracket (**PFM**) and Passenger Front Support Bracket (**DFS/PFS**) with (2) M10X1.5-30mm Hex Bolts, (4) M10 Large Flat Washers, (2) M10 Lock Washers and (2) M10 Hex Nuts, (**Fig 1**). Do not fully tighten hardware at this time.




(Fig 1) Passenger Side Front Brackets Assembly

STEP 3

Attach the assembled Passenger Front Mounting Bracket **(PFM)** to the vehicle with factory bolt, **(Fig 2 & 3)**.

Attach Passenger Front Support Bracket (**DFS/PFS**) to smaller factory hole in the frame using (1) M12X1.75-100mm Hex Bolt, (1) M12 Nylon Lock Nut, (2) M12 Large Flat Washers, (**Fig 2 & 3**). Do not fully tighten hardware at this time.




(Fig 2) Passenger Side Front Brackets Installation

STEP 4

Move to the passenger side rear mounting location. Remove the passenger rear body mount bolt.

STEP 5

Assemble Passenger Rear Mounting Bracket (**PRM**) and Passenger Rear Support Bracket (**PRS**) with (1) M10X1.5-30mm Hex Bolt, (2) M10 Large Flat Washers, (1) M10 Lock Washer and (1) M10 Hex Nut, (**Fig 3**). Do not fully tighten hardware at this time.



(Fig 3) Passenger Side Rear Brackets Assembly

Customer Support: info@iboardauto.com

3 Rev. 20230401

i Board®



STEP 6

Attach the assembled Passenger Rear Mounting Bracket (PRM) to the vehicle with factory bolts, (Fig 4 & 5).


Attach Passenger Rear Support Bracket (**PRS**) to the factory hole on the inner side of body mount cavity and closer to the frame using:

05-07 Models:


(1) M8X1.25-25mm Hex Bolt, (1) M8 Nylon Lock Nut, (2) M8 Large Flat Washers (Fig 4). Do not fully tighten hardware at this time.

08-On Models:

(1) M6X1-30mm Hex Bolt, (1) M6 Nylon Lock Nut, (2) M6 Flat Washers (Fig 5). Do not fully tighten hardware at this time.



(Fig 4) Passenger Side Rear Brackets Installation (05-07 Models)



(Fig 5) Passenger Side Rear Brackets Installation (08-On Models)

STEP 7

Once all (2) Passenger side mounting brackets are installed, then proceed to the Step Bar installation. (Figs 6 & 7)

- (1) Select (1) Slider and (2) M8X1.25-35mm Carriage Bolts;
- (2) Install (2) M8X1.25-35mm Carriage Bolts in (1) Slider.
- (3) Slide the Slider (with carriage bolts) to the **Step Bar.**
- (4) Repeat to install the other (1) slider to the step bar.
- (5) Attach the Step Bar (with the Sliders) onto the installed mounting brackets. Position the Sliders to the installed brackets. Secure the Step Bar to the installed Brackets by using (4) M8 Large Flat Washers and (4) M8 Nylon Lock Nuts and (2) Sliders, (Fig 7). Do not fully tighten hardware at this time.

Note: The Sliders are packed with the Step Bars.

Level and adjust the Step Bar and fully tighten all hardware.

Repeat **Steps 1-7** for the other side Step Bar installation. **The installation is completed!!!**

Attention

Do periodic inspections to the installation to make sure that all hardware is secure and tight.

In order to protect your bars/boards, please use mild soap/non-abrasive products for cleaning only.

Customer Support: info@iboardauto.com

4 Rev. 20230401

iBoard[®]



