


iBoard[®] by APS

PART#: IB-369C&H



iBoard[®]




Hardware Package A (For Bracket Installation)										
ltem	QTY	Description	ltem	QTY	Description					
1#	12	M10X35 Bolt Plates	6#	14	M10X1.5 Hex Nuts					
2#	2	M10X35 Long Bolt Plates	7#	2	M8X1.25-25mm Hex Bolts					
3#	14	M10 Plastic Washers	8#	4	M8 Flat Washers					
4#	14	M10 Flat Washers	9#	2	M8 Lock Washers					
5#	14	M10 Lock Washers	10#	2	M8X1.25 Hex Nuts					
1# 2# 3# 4# 5# 6# 7# 8# 9# 10#										

	Hardware Package B (For Stainless Steel Step Bar Installation)									
ltem	QTY	Description	ltem	QTY	Description					
1#	12	M8X1.25-35mm Carriage Bolts	3#	12	M8 Nylon Lock Nuts					
2#	12	M8 Large Flat Washers	4#	6	Sliders (Packed with Step Bars)					
1# 2#			3# 4#							



STEP 1


Start the installation from the Passenger Side Front Mounting Location of the vehicle. Locate and remove the plastic covers at the bottom of the vehicle, (Fig 17). Remove the plugs covering the mounting holes on the mounting location, (Fig 1).



(Fig 1) Passenger Side Front Mounting Location


STEP 2

Insert (2) M10X35 Bolt Plates into the (2) mounting holes, (Figs 1, 2).



STEP 3


Select the Passenger Front Mounting Bracket (**PFM**), attach the Bracket to the installed M10X35 Bolt Plates with (2) M10 Plastic Washers, (2) M10 Flat Washers, (2) M10 Lock Washers and (2) M10X1.5 Hex Nuts, (Fig 3). Do not fully tighten at this time.



(Fig 3) Passenger Front Mounting Bracket Installation

STEP 4


Move to the Passenger Side Center Mounting Location, (Figs 4 -6). Repeat Steps 1-3 to attach the Passenger Center Mounting Bracket to the center mounting location, (Fig 7). Do not fully tighten at this time.



(Fig 4) Passenger Side Center Mounting Location


iBoard[®]





STEP 5

Move to the Passenger Side Rear Mounting Location, (Fig 8). Insert (1) M10X35 Long Bolt Plate into the large hole in the floor panel, (Fig 9). Insert (2) M10X35 Bolt Plates into the smaller holes beside the M10X35 Long Bolt Plate, (Fig 9).




STEP 6

Select the Passenger Rear Mounting Bracket (**PRM**), attach the Bracket to the installed M10X35 Bolt Plate and M10X35 Long Bolt Plate with (2) M10 Plastic Washers, (2) M10 Flat Washers, (2) M10 Lock Washers and (2) M10X1.5 Hex Nuts, (**Fig 10).** Do not fully tighten at this time.



Installation Video





(Fig 10) Passenger Rear Mounting Bracket Installation

STEP 7

Select the Passenger Rear Support Bracket (**PRS**), secure the Passenger Rear Support Bracket (**PRS**) to the Passenger Rear Mounting Bracket (**PRM**) with (1) M8X1.25-25mm Hex Bolt, (2) M8 Large Flat Washers, (1) M8 Lock Washer and (1) M8X1.25 Hex Nut, (**Figs 11 & 12**). Do not fully tighten at this time.

Attach the other side of the support bracket to the installed M10X35 Bolt Plate with (1) M10 Plastic Washer, (1) M10 Flat Washer, (1) M10 Lock Washer and (1) M10X1.5 Hex Nut, **(Fig 12).** Do not fully tighten at this time.





(Fig 12) Passenger Rear Support Bracket Installation

STEP 8

Once all (3) Passenger side mounting brackets are installed, then proceed to the Step Bar installation. (Figs 13 & 14)

(1) Select (1) Slider and (2) M8X1.25-35mm Carriage Bolts;

(2) Install (2) M8X1.25-35mm Carriage Bolts in (1) Slider.

(3) Slide the Slider (with carriage bolts) to the Step Bar.

(4) Repeat to install the other (2) sliders to the step bar.

(5) Attach the Step Bar (with the Sliders) onto the installed mounting brackets. Position the Sliders to the installed brackets. Secure the Step Bar to the installed Brackets by using (6) M8 Large Flat Washers and (6) M8 Nylon Lock Nuts and (3) Sliders, (**Fig 14**). Do not fully tighten hardware at this time.

Note: The Sliders are packed with the Step Bars.

Level and adjust the Step Bar and fully tighten all hardware.

STEP 9

Line up the factory plastic covers up to the original mounting locations. Mark the Mounting Brackets positions on the cover. Cut the interference on the cover according to the marks of the brackets. Reinstall the plastic cover to the bottom of the vehicle, (Fig 15). The installation is completed.



